

# Trimble Dini DIGITAL LEVEL

DATASHEET

## KEY FEATURES

Determine accurate height information via a quick and easy key press

Eliminate errors and reduce rework with digital readings

Enjoy effortless data transfer between instrument and office

Measure to a measurement field of just 30 cm

Level 60% faster than with conventional automatic leveling

The Trimble DiNi<sup>®</sup> Digital Level is a digital height measurement sensor from Trimble's Integrated Surveying portfolio of products. The Trimble DiNi is a field-proven tool designed for any job site where fast and accurate height determination is required. Use the Trimble DiNi for applications such as precise leveling of flat and sloping surfaces, establishing the vertical component of grade and ground profiles, subsidence monitoring, and establishing the vertical component of control networks.

## UNEQUALLED for PERFORMANCE in THE FIELD

The Trimble DiNi is designed to perform optimally every day, whatever your surveying job. It is built rugged—with a dust- and waterproof rating of IP55—to take the tough conditions of the job site in its stride. A backlight in the screen and a light in the circular bubble keep you productive even when daylight gets low.

The DiNi will operate for three days without requiring a battery change, then when it does just recharge it as you would your Trimble GNSS system battery...the batteries are the same to ensure convenience and productivity.

When a job is complete, easily transfer data from the instrument to a computer by using a USB storage device; You don't have to carry your instrument in to the office.

## EASY To LEARN, EASY To USE

The Trimble DiNi Digital Level demands the industry's smallest measurement field—just 30 cm of code rod. So you can measure greater change in height between the level and the rod in one setup, and save time. Additionally, the small measurement area:

- reduces the number of stations needed by up to 20% because the Trimble DiNi is less impacted by a rod hidden by vegetation or hilly terrain.
- makes leveling in low light conditions, for example, in tunnels, easier because only a very small part of the staff needs to be illuminated.
- ensures greater accuracy through less influence of refraction near the ground.

The large graphical display of the Trimble DiNi is also unique, and is complemented by the latest Trimble keyboard for easy operation. Crew members used to operating other Trimble systems will easily adapt to the Trimble DiNi.

## TRIMBLE QUALITY AND ACCURACY for MEASURING WITH CONFIDENCE

The Trimble DiNi Digital Level is designed to support the rest of Trimble's Integrated Surveying portfolio. The Trimble DiNi interface is based on Trimble's other advanced and field-proven controllers for easy adoption of the instrument by your crews. Proven Optics by Carl Zeiss ensure the Trimble DiNi offers the highest precision and best resolution.

Measure with confidence, knowing that with the Trimble DiNi Digital Level, your crew will obtain the best quality results with the highest level of productivity.



# Trimble Dini DigiTAL iLeVEl

## performance specifications

Accuracy .....DIN 18723, standard deviation height measuring  
per 1 km (3280.84 ft) of double leveling

### trimble Dini 0.3 mm per km

Electronic measurement  
Invar precision bar code staff ..... 0.3 mm (0.001 ft)  
Standard bar code staff ..... 1.0 mm (0.004 ft)  
Visual measurement ..... 1.5 mm (0.005 ft)  
Distance measurement ..... with a 20 m (65.62 ft) sighting distance  
Invar precision bar code staff ..... 20 mm (0.066 ft)  
Standard bar code staff ..... 25 mm (0.082 ft)  
Visual measurements ..... 0.2 m (0.656 ft)

### trimble Dini 0.7 mm per km

Electronic measurement  
Invar precision bar code staff ..... 0.7 mm (0.002 ft)  
Standard bar code staff ..... 1.3 mm (0.004 ft)  
Visual measurement ..... 2.0 mm (0.007 ft)  
Distance measurement ..... with a 20 m (65.62 ft) sighting distance  
Invar precision bar code staff ..... 25 mm (0.082 ft)  
Standard bar code staff ..... 30 mm (0.098 ft)  
Visual measurement ..... 0.3 m (0.984 ft)

### range

Electronic measurement ..... 1.5 m–100 m (4.92 ft–328.08 ft)  
Visual measurement ..... from 1.3 m (4.265 ft)

### electronic measurement

trimble Dini 0.3 mm per km  
Resolution height measurement ..... 0.01 mm / 0.0001 ft / 0.0001 in  
Resolution distance measurement ..... 1 mm (0.003 ft)  
Measurement time ..... 3 s

### trimble Dini 0.7 mm per km

Resolution height measurement ..... 0.1 mm / 0.001 ft / 0.001 in  
Resolution distance measurement ..... 10 mm (0.033 ft)  
Measurement time ..... 2 s

### Horizontal circle

Type of graduation ..... 400 grads and 360 deg  
Graduation interval ..... .1 grad and 1 deg  
Estimation to ..... .0.1 grad and 0.1 deg

### measurement programs

trimble Dini 0.3 mm per km  
Standard programs ..... Single measurement with and without stationing,  
stakeout, line leveling with intermediate sight  
and stakeout, line adjustment  
Leveling methods ..... BF, BFFB, BFBF, BBFF, FBBF  
aBF, aBFFB, aBFBF, aBBFF, aFBBF

### trimble Dini 0.7 mm per km

Standard programs ..... Single measurement with and  
without stationing, stakeout, line leveling with  
intermediate sight and stakeout  
Leveling methods ..... BF, BFFB, aBF, aBFFB

Footnote 1: F = Foresight, B = Backsight, a = alternating  
Certified quality in accordance with DIN ISO 9001/EN 29001.

© 2001–2013, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, and Dini are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Integrated Surveying is a trademark of Trimble Navigation Limited. All other trademarks are the property of their respective owners. PN 022543-327C (07/13)

## enVironmental

Operating temperature ..... –20 °C to +50 °C (–4 °F to 122 °F)  
Dust- and waterproofing ..... IP55

## General specification

telescope  
Aperture ..... 40 mm (0.131 ft)  
Field of view at 100 m ..... 2.2 m (7.217 ft)  
Electronic measurement field ..... 0.3 m (0.984 ft)  
Magnification  
Trimble DiNi 0.3 mm per km ..... 32 x  
Trimble DiNi 0.7 mm per km ..... 26 x

### compensator

Inclination range ..... ±15'  
Setting accuracy  
Trimble DiNi 0.3 mm per km ..... ±0.2"  
Trimble DiNi 0.7 mm per km ..... ±0.5"  
Circular level ..... 8/2 mm with illumination

Display ..... Graphical, 240 x 160 pixels, monochrome with illumination

Keyboard ..... 19-key alpha-numeric and 4-way arrow key for navigation\

### recording

Internal memory ..... up to 30 000 data lines  
External memory ..... USB Flash Drive support  
Data transfer ..... USB Interface for data transfer between DiNi and PC  
(means two way communication)

### Real-time clock and temperature sensor

Trimble DiNi 0.3 mm per km ..... Recording of time or temperature  
Trimble DiNi 0.7 mm per km ..... N.A.

### Power supply

Internal battery ..... Li-Ion, 7.4 V / 2.4 Ah  
Operating time ..... 3 days working time without illumination  
Weight (including battery) ..... 3.5 kg (7.72 lb)



Specifications subject to change without notice.

## NORTH AMERICA

Trimble Navigation Limited  
10368 Westmoor Dr  
Westminster CO 80021  
USA

## EUROPE

Trimble Germany GmbH  
Am Prime Parc 11  
65479 Raunheim  
GERMANY

## ASIA-PACIFIC

Trimble Navigation  
Singapore Pty Limited  
80 Marine Parade Road  
#22-06, Parkway Parade  
Singapore 449269  
SINGAPORE



TRIMBLE AUTHORIZED DISTRIBUTION PARTNER

